



Step 1. PFD, MFD Reversion

On occasion the Jeppesen charts can lock up on the MFD. Use the following steps to troubleshoot and clear the charts lock up issue that may be related to the Chart Preset condition that can sometimes occur. Doing a display reversion should restore chart menu status to FMSx.

By following these steps you should be able to clear the MFD from using a default value of Chart Preset to reestablish the FMS/Chart database link and retrieve charts from the FSU. Note: Manual selection of a chart is possible in Chart Preset from the "OTHER AIRPORT" selection of the Chart Main Index.



 With avionics power on find the reversionary switch for MFD/PFD displays and put the displays in the revisionary mode so the MFD screen is blank. After a few seconds revert the displays back to normal.





MFD Reset

- The display reversion switch is used to power-down a failed display, and to show combined PFD/MFD format on the remaining display. This is the only way to clear the MFD from using a default value of Chart Preset affecting the charts being displayed as well as the inability to scroll the focus box on some IFIS pages.
- The reversion procedure can be accomplished in flight if needed.





Step 2. Clear Remaining FMS Flight Plans

To reestablish the chart link between the FMS database and Jeppesen charts database you must do the following:

- Verify the that the FMS position is at your current location or set a position initialization in the FMS using your airport identifier.
- Enter you're airport identifier in the flight plan page then complete inputting a flight plan with destination, runways and an approach at the destination.



Rockwell Collins

On the flight plan page enter your ORIGIN airport ICAO identifier, DEST airport and copy the destination to the TO block and EXICUTE the flight plan.

Θ	ACT FPLN 1/2
	KCID 913 KSLC
	ROUTE ALTN
	ORIG RWY
	VIA
	DIRECT KSLC
	<copy active<="" td=""></copy>
	<sec fpln="" init="" perf=""></sec>
MSG	EXEC
DIR FF	PLN LEGS DEP ARR PERF MFD MFD MFD PREV NEXT
	56HIJKLMN
50	890PQRSTU
20	Ø +/- V W X Y Z SP /

ш	1050 PROP 1050 ITT > 200 FF 2	200	
40		00	
TORO	68.0 N1 68.0 TEMP °C	89	
27			
	CHART MAIN INDEX		
	FMS1		
	DRIGIN - KCID		
	AIRPORT [AIRPORT, PARKING, AIRPORT INFO, TAKE]		
	ARRIVAL		
	APPROACH []		
	CHART NOTAMS	1.5	
	DESTINATION - KSLC	1	
	ARRIVAL []		
	APPRUACH [] AIRPORT [AIRPORT]		
	DEPARTURE []		
	ANY CHART [] CHART NOTAMS	61	
	ALTERNATE		
\$	ANY CHART	>	
	ANY CHART		
	NTHER ATRENET	ET	
	ANY CHART	5	
	ANY CHART	-	





Step 3. Checking for Proper Chart Operation

- Using the cursor control panel, press the chart button then the menu button and observe if the airport identifier is displayed in the ORGIN block at the top of the page.
- Scroll the focus box to a magenta line on the chart main index and select a chart

 2		
MENU ESC STAT	MEM1	CHART
	MEM2	
(The second	MEM3	ZOOM Collins
_	_	

• /_		Collins
I	1050 PROP 1050 ITT 400 568.0 N1 68.0 27.0 100 PRESS 0IL 89 TEMP °C 27.0	200 100 89
	CHART MAIN INDEX	
	FMS1	
	DRIGIN - KCID	
	AIRPORT [AIRPORT, PARKING, AIRPORT INFO, TAKE] DEPARTURE	
	ARRIVAL APPRDACH [] ANY CHART [] CHART NDTAMS	
	DESTINATION - KSLC	
	ARRIVAL [] APPRDACH [] AIRPORT [AIRPORT]	
	DEPARTURE [] ANY CHART [] CHART NOTAMS	
-	ALTERNATE	
	ANY CHART ANY CHART CHART NOTAMS	
7	OTHER AIRPORT	
	ANY CHART ANY CHART CHART NUTANS	
	CHART DIMMING DAY NIGHT	
		BRT
		DIM



Rockwell Collins

Step 3. Continued

When the flight plan with airports, runways and procedures is populated on the Chart Main Index you should be able to scroll to the menu option and select the charts for airport diagrams, DEP, STARs and Terminal Procedures.

	and the second second
	FMS1
ORIGIN - KCID	
AIRPORT [AIRPORT, PARKING, AIRPORT INFO DEPARTURE	, TAKE
ARRIVAL APPRDACH [] ANY CHART [] CHART NOTAMS	
DESTINATION - KPVU	
ARRIVAL APPROACH [ILS OR LOC DME RWY 13] AIRPORT [AIRPORT]	
DEPARTURE [] ANY CHART [] CHART NOTAMS	
ALTERNATE	
ANY CHART ANY CHART CHART NOTAMS	
OTHER AIRPORT - C16	
ANY CHART [] ANY CHART [] CHART NOTAMS	
CHART DIMMING DAY NIGHT	







Resetting the Jeppesen Subscription Serial No.

This is an optional step and most of the time step 3 resolves the issue.

If the field is all dashes, you may need to reload the chart database, then reset avionics power or FSU circuit breaker to reboot the File Server Unit computer. If you don't have the Jeppesen subscription key serial number you will need to contact Jeppesen at 303.328.4244 or in the U.S. 800.553.7750.

If you need to reenter the 16 character Jeppesen chart subscription key serial number on the chart subscription page continue to the next step.

